

EXTRAFLEX

04-311 SPECIFICATION SHEET

COATING

Black **HCT** MicroFoam

Nitrile Palm Coating











FEATURES:

ATTRIBUTES:

13g, Blue Cut Resistant/ Engineered Yarn Liner,

Poly-Acrylic Fleece Liner

LINER

ANSI Cut Level A4 EN388 Cut Level 4 "All in One": Fit, Feel, Flexibility, Breathability, Durability Excellent Wet Grip

CATEGORY:

Extraflex

APPLICATIONS:

Cold Storage Fishing Outdoor Winter Work Landscaping

Armor Guys reference number: 04-311

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES: Hybrid Coalling Technology

SPECIFICATIONS

LINER MATERIALS	13g, Blue Engineered Yarn Liner			
COATING MATERIALS	Black HCT MicroFoam Nitrile			
WRIST DESIGN	Continuous Knit			
SIZES	S-XXXL			

PACKAGING							
CASE SIZE	S	М	L	XL	XXL	XXXL	
PER CARTON	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ	
CUFF COLOR	■Red	Yellow	Brown	■Black	Blue	■Gray	
ORIGIN	PRC						

PERFORMANCE LEVEL

EN388: 4443D	EN Level 4 Cut Resistance							
ABRASION	0	1	2	3	4	5		
CUT	0	1	2	3	4	5		
TEAR	0	1	2	3	4	5		
PUNCTURE	0	1	2	3	4	5		
CUT TDM TEST	Α	В	С	D	Е	F		